



## Grid Tied Inverter

Three Phase: GT3-4K/5K/6K/8K/10K/12K/15K/17K/20K/22K/25K D1

The LIVOLTEK GT3-4/5/8/10/12/15/17/20/22/25K-D1 PV inverter is developed for residential or commercial customers who need a three-phase rooftop model. The Shade Fix integrated shading management system ensures that the inverter maximizes energy production even when the PV panels are lightly shaded. The machine has a built-in optional AFCI module to prevent electrical fires caused by abnormal arc faults in the electrical wiring, with a high safety factor. With 160V ultra-low start-up voltage, ultra-long working time, it's surely an ideal choice for large commercial and industrial power plants.



### Features

- 150% DC/AC ratio
- External LCD display box
- Export limitation (optional)
- Smart APP to monitor & optimize
- AFCI (optional)
- Plug-and-play installation saves time
- 110% AC output for efficient power generation



Max Efficiency 98.6%



Support Export Limitation



IP65 C5 Anti-corrosion



SPD II Protection

### Compatible Products



LCD Screen



PSD200-FI Dongle



Smart Meter



Monitoring System

# Specifications

Model	GT3-4KD1	GT3-5KD1	GT3-6KD1	GT3-8KD1	GT3-10KD1	GT3-12KD1	GT3-15KD1	GT3-17KD1	GT3-20KD1	GT3-22KD1	GT3-25KD1	
<b>Input(PV)</b>												
Max. DC Input Power	6000Wp	7500Wp	9000Wp	12000Wp	15000Wp	18000Wp	22500Wp	25500Wp	30000Wp	33000Wp	37500Wp	
Max. DC Input Voltage	1100V											
Min PV Input Voltage	140V											
Start-up DC Input Voltage	160V											
Nominal DC Input Voltage	650V											
MPPT Operating Range	140V-1000V											
Max. DC Input Current	16A+16A				40A+20A				40A+40A			
Max. Short Circuit Current	21A+21A				52A+26A				52A+52A			
No. of MPPTs	2				2				2			
No. of Strings per MPP Trackers	1/1				2/1				2/2			
<b>Output (AC)</b>												
Nominal Output Power	4000W	5000W	6000W	8000W	10000W	12000W	15000W	17000W	20000W	22000W	25000W	
Max. Apparent Power	4400VA	5500VA	6600VA	8800VA	11000VA	13200VA	16500VA	18700VA	22000VA	24200VA	27500VA	
Rated AC Grid Output Current	5.8A	7.2A	8.7A	11.5A	14.4A	17.3A	21.7A	24.5A	28.9A	31.8A	36.1A	
Max. AC Output Current	6.4A	7.9A	9.5A	12.7A	15.9A	19.1A	23.8A	27.0A	31.8A	34.9A	39.7A	
Rated AC Grid Voltage	3/N/PE, 220V/380V, 230V/400V											
AC Grid Voltage Range	270V-480V											
Rated Grid Frequency	50Hz/60Hz											
Grid Frequency Range	45Hz-55Hz/55Hz-66Hz											
Power Factor	> 0.99 Rated Power (Adjustable 0.8 Leading - 0.8Lagging)											
Output THDi (@Nominal Output)	<3%											
<b>Efficiency</b>												
Max. Efficiency	98.50%	98.50%	98.50%	98.60%	98.60%	98.60%	98.50%	98.50%	98.60%	98.60%	98.60%	
Euro Efficiency	98.10%	98.10%	98.10%	98.20%	98.20%	98.20%	98.10%	98.10%	98.20%	98.20%	98.20%	
MPPT Efficiency	>99%											
<b>Protection</b>												
Surge Arrester	Type II											
PV Current Detection	Support											
Over Current Protection	Support											
AC Short Circuit Protection	Support											
Over Voltage Protection	Support											
Anti-islanding Protection	Support											
Residual Current Monitoring Unit	Support											
Integrated AFCI (Arc-Fault Circuit Protection)	Optional											
<b>General Data</b>												
Dimension (W*H*D)	520*420*193mm											
Weight	22kg					24.5kg						
Protection Degree	IP65					IP65						
Cooling	Natural Cooling					Fan Cooling						
Operating Temperature Range	-30℃~ 60℃ (Derating at 45℃)					-30℃~ 60℃ (Derating at 45℃)						
Typical Noise Emission	<30dB					<40dB						
Night Self Consumption	<1W											
Display	LED+APP/ LCD (Optional)											
Communication	RS485(LCD/Meter), 4G/Wi-Fi+Bluetooth, DRM											
<b>Certifications and Standards</b>												
Grid Regulation	IEC61727, IEC62116, CQC ABNT NBR 16149, ABNT NBR 16150											
Safety/EMC	IEC62109-1/2, EN61000-6-1/2/3/4											
Standard Warranty	5 Years/10 Years (Optional)											